



Merlin[®]
the automatic choice

MJ3800



DOOR TYPES: residential sectional doors **DOOR SIZE:** doors up to 16.5m²

Key Benefits

Compliant to Australian and New Zealand Standard AS/NZS 60335-2-95 

Soft Start/Stop Function

The MJ3800 is equipped with Soft Start/Stop technology, designed to ensure smooth and quiet door operation.

Accessories Included

This opener features two hand-held mini transmitters deluxe wall control, IR Beams, solenoid lock, wireless wall button and battery backup.

Auto-close

Automatically closes door after a pre-determined delay time. Requires installation of IR Beams – supplied.

Additional safety feature

To ensure the highest level of safety possible the MJ3800 is supplied with a cable tension monitor which prevents the opener operating if the door's safety cable has insufficient tension.

Electric locking

For additional peace of mind this opener is supplied with a solenoid lock which automatically locks the door when it is closed and releases on activation.

5 Year Warranty

Backed by a full 2 year / 5,000 cycle unit warranty and a 5 year / 10,000 cycle motor warranty** we stand behind our products with an after sales support team that we believe are the best in the industry.

COMPLIANT TO AUSTRALIAN AND NEW ZEALAND STANDARDS

Standard Merlin Safety Features

Premium Automatic Safety Reverse

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up.

Automatic Force Sensing

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door.

Manual Release

In case of power failure you can simply activate the manual release to open your garage door.

*when compared to other available products ** conditions apply



Kit Contents



1 x Powerhead



Evercharge standby power unit CM475



2 x Three channel key ring mini-transmitters C945



Wireless wall button CM128



Deluxe wall control C845



Cable Tension Monitor



Solenoid lock



Protector System safety beam sensors C77

SPECIFICATIONS

- 24V DC motor with thermal overload protection
- Input voltage: 230/240V AC
- Rated door area up to 16.5m²
- Max door weight: up to 130kg
- Max peak pulling force: 600 N
- 433.92 MHz AM radio with Chamberlain Peak Detect™ rolling code technology
- Up to 64 memory registers